

Trade name: WIDOPUR-primer LF 2K - Komponente B

Current version: 2.3.0, issued: 11.06.2021 Replaced version: 2.2.0, issued: 12.04.2021 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

WIDOPUR-primer LF 2K - Komponente B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Polyurethane component

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

Widopan Produkte GmbH

Ostereichen 3

D-21714 Hammah

Telephone no. +49 (0) 4144 69821-0 Fax no. +49 (0) 4144 69821-20

Information provided by / telephone

+49 (0) 4144 69821-0

Advice on Safety Data Sheet

sdb_info@umco.de

Details of the importer

Address

Widopan Limited

System House

Horndon Industrial Park

24 Station Rd

West Horndon

Brentwood

CM13 3XL

1.4 Emergency telephone number

For medical advice (in German and English): +49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Acute Tox. 4; H332

Carc. 2; H351

Eye Irrit. 2; H319

Resp. Sens. 1; H334

Skin Irrit. 2; H315

Skin Sens. 1; H317

STOT RE 2; H373

STOT SE 3; H335

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.



Trade name: WIDOPUR-primer LF 2K - Komponente B

Current version: 2.3.0, issued: 11.06.2021 Reglaced version: 2.2.0, issued: 12.04.2021 Region: GB

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms





GHS07

Signal word

Danger

Hazardous component(s) to be indicated on label:

diphenylmethanediisocyanate, isomeres and homologues

Hazard statement(s)

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure

Hazard statements (EU)

EUH204 Contains isocyanates. May produce an allergic reaction.

Precautionary statement(s)

P201 Obtain special instructions before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 In case of inadequate ventilation wear respiratory protection.
P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container to a facility in accordance with local and national

regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Mixture (preparation)

Hazardous ingredients

Tidada da da Tilgi da ti						
No	Substance name		Additional information			
	CAS / EC / Index /	Classification (EC) 1272/2008 (CLP)	Conce	entration		%
	REACH no	· , , , , , , , , , , , , , , , , , , ,				
1	diphenylmethaned	iisocyanate, isomeres and homologues				
	9016-87-9	Carc. 2; H351	>=	50.00 - <	70.00	wt%
	-	Acute Tox. 4; H332				
	-	STOT SE 3; H335				
	-	STOT RE 2; H373				
		Eye Irrit. 2; H319				
		Skin Irrit. 2; H315				



Trade name: WIDOPUR-primer LF 2K - Komponente B

Current version: 2.3.0, issued: 11.06.2021 Replaced version: 2.2.0, issued: 12.04.2021 Region: GB

	Resp. Sens. 1; H334	
	Skin Sens. 1; H317	

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
1	-	Resp. Sens. 1; H334: C >= 0.1%	-	-
		Eye Irrit. 2; H319: C >= 5%		
		STOT SE 3; H335: C >= 5%		
		Skin Irrit. 2; H315: C >= 5%		

No	Route, target organ, concrete effect
1	H373
	inhalational; hearing; -

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. If the patient is likely to become unconscious, place and transport in stable sideways position.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air. Irregular breathing/no breathing: artificial respiration. Call a doctor immediately.

After skin contact

Wash off immediately with soap and water. Consult a doctor if skin irritation persists.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). Seek medical assistance.

After ingestion

Do not induce vomiting. Rinse out mouth and give plenty of water to drink. Never give anything by mouth to an unconscious person. Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Water spray jet; Carbon dioxide

Unsuitable extinguishing media

No data available.

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO); Isocyanate vapours. Traces of hydrogen cyanide. Nitrogen oxides (NOx)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Cool endangered containers with water spray jet. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



Trade name: WIDOPUR-primer LF 2K - Komponente B

Current version: 2.3.0, issued: 11.06.2021 Reglaced version: 2.2.0, issued: 12.04.2021 Region: GB

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Cover up with damp, liquid absorbing material (e. g. sawdust, chemical binding material based on calcium silicate hydrate, sand). After 1 hour collect in stainless containers for waste material disposal. Do not seal containers (generation of CO2)! Keep damp and let stand in a secured outdoor location for several days. Dispose according to section 13. Clean contaminated surfaces thoroughly with water. With a solution of 5 - 10 % sodium, 0.2 - 2 % detergents and 90 - 95 % water to neutralize.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation. When filling, transferring, or emptying of containers, adequate suctioning close to work place necessary. Provide suitable exhaust ventilation at the processing machines. If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Wash hands before breaks and after work. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Precautions should be taken to minimise exposure to atmospheric humidity or water: CO2 will be formed which in closed containers can result in pressurisation. DO NOT KEEP THE CONTAINERS SEALED!! Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Keep only in the original container. Cover opened container with nitrogen in order to keep moisture away from the product.

Appropriate Material iron; HDPE; LDPE; tin; stainless steel

Incompatible products

Do not store together with: Keep away from water. Alcohols; Amines; Acids; Bases; Alkalies

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.	



Trade name: WIDOPUR-primer LF 2K - Komponente B

Current version: 2.3.0, issued: 11.06.2021 Replaced version: 2.2.0, issued: 12.04.2021 Region: GB

1	diphenylmethanediisocyanate, isomeres and	9016-87-9	
	homologues		
	List of approved workplace exposure limits (WELs) /	EH40	
	Isocyanates, all (as -NCO) Exept methyl isocyanate		
	WEL short-term (15 min reference period)	0.07	mg/m³
	WEL long-term (8-hr TWA reference period)	0.02	mg/m³
	Comments	Sen	

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

In case of insufficient ventilation and during spray application respiratory protection necessary. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified. Short term: filter apparatus, combination filter A-P2

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness	batyrrabbor	0.7	mm
	_		
Breakthrough time	>	480	min
Appropriate Material	nitrile rubber		
Material thickness		0.4	mm
Breakthrough time	>	480	min
Appropriate Material	chloroprene		
Material thickness		0.5	mm
Breakthrough time	>	480	min
Inappropriate material	PVC		
Material thickness		0.7	mm

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation	
liquid	
Form/Colour	
liquid	
brown	
Odour	
Earthy; musty	

Boiling point / boiling range

pH value
No data available



Trade name: WIDOPUR-primer LF 2K - Komponente B

Current version : 2.3.0, issued: 11.06.2021	Replaced version: 2.2.0, issued: 12.04.2021	Region: GB
--	--	------------

Value		330	°C
Reference pressure		1013	hPa
Melting point/freezing point			
Value	<	10	°C
Decomposition temperature			
Value	>	230	°C
Flash point			
Value	>	200	°C
Source	Literature value		
Ignition temperature			
Value	>	600	°C
Flammability	,		
No data available			
Lower explosion limit No data available			
Upper explosion limit No data available			
Vapour pressure Value	<	0.01	Pa
Reference temperature	`	25	°C
·			_
Relative vapour density No data available			
Relative density No data available			
Density		4.00	
Value Reference temperature		1.22 25	g/cm³ °C
•		20	<u> </u>
Solubility in water Comments	bydrolyggg		
Comments	hydrolyses Reacts with wate	r	
	Trodoto with water		
Solubility No data available			
Partition coefficient n-octanol/water (log	value)		
No data available			
Viscosity		100	
Value Reference temperature	90 -	130 25	mPa*s °C
Type	dynamic	23	O .
	1 = 7.1.2.1110		
Particle characteristics No data available			
NO Uata avallable			

9.2 Other information

Other information	
No data available.	

SECTION 10: Stability and reactivity

10.1 Reactivity

no corrosive behaviour to metals



Trade name: WIDOPUR-primer LF 2K - Komponente B

Current version: 2.3.0, issued: 11.06.2021 Replaced version: 2.2.0, issued: 12.04.2021 Region: GB

10.2 Chemical stability

Stable if stored and handled properly.

10.3 Possibility of hazardous reactions

Reaction with water to form carbon dioxide. Reaction with substances containing active hydrogen.

10.4 Conditions to avoid

Moisture. Heat

10.5 Incompatible materials

Alcohols; Acids; Amines; Water; Alkalies

10.6 Hazardous decomposition products

In case of fire the following can be released: Isocyanate vapours; Traces of hydrogen cyanide

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acu	Acute oral toxicity					
No	Product Name					
1	WIDOPUR-primer LF 2K - Komponente I	3				
LD50		>	10000	mg/kg		
Species		rat				

Acu	Acute dermal toxicity			
No	Product Name			
1	WIDOPUR-primer LF 2K - Komponente B			
LD5	0	>	10000	mg/kg
Species		rabbit		

Acut	Acute inhalational toxicity (result of the ATE calculation for the mixture)			
No	Product Name			
1	WIDOPUR-primer LF 2K - Komponente B			
ATE	ATE (Mixture) 20.0000 mg/l			
Route of exposure / physical from		Vapour		
		Calculation method according Regulation (EC) No 1272/2008, (CLP), annex I, part 3, section 3.1.3.6.		

Acu	Acute inhalational toxicity			
No	Product Name			
1	WIDOPUR-primer LF 2K - Komponente E	3		
LC5	0	appr.	0.493	mg/l
Duration of exposure			4	h
Spec	cies	rat		

Skir	Skin corrosion/irritation			
No	Product Name			
1	WIDOPUR-primer LF 2K - Komponente B			
Evaluation irritant		irritant		

Seri	Serious eye damage/irritation			
No	Product Name			
1	WIDOPUR-primer LF 2K - Komponente B			
Eval	uation	irritant		

Res	Respiratory or skin sensitisation		
No	Product Name		
1	WIDOPUR-primer LF 2K - Komponente B		
Rout	te of exposure	Skin	
Eval	uation	sensitizing	



Trade name: WIDOPUR-primer LF 2K - Komponente B

Current version: 2.3.0, issued: 11.06.2021 Replaced version: 2.2.0, issued: 12.04.2021 Region: GB

Germ cell mutagenicity

No data available

Reproduction toxicity

No data available

Carcinogenicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

In case of overexposure – especially during spraying applications without observed safety measures – danger of eye, nose, throat and airways irritation. Delayed appearance of difficulties and development of hypersensitivity (difficult breathing, coughing, and asthma) are possible. There may be hypersensitive persons who develop reactions following exposure to very low concentrations of isocyanates, even below the threshold limit value at the workplace. Tanning and irritating effects are possible at prolonged skin contact.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxi	Toxicity to fish (acute)			
No	Product Name			
1	WIDOPUR-primer LF 2K - Komponente B			
LC0 > 1000			mg/l	
Duration of exposure			96	h

Toxicity to fish (chronic)	
No data available	

Toxi	Toxicity to Daphnia (acute)			
No	Product Name			
1	WIDOPUR-primer LF 2K - Komponente B			
EC0	EC0 > 500 mg/l			
Duration of exposure			24	h

Toxicity to Daphnia (chronic)	
No data available	

Toxi	Toxicity to algae (acute)			
No	Product Name			
1	WIDOPUR-primer LF 2K - Komponente B	3		
EC0			1640	mg/l
Duration of exposure			72	h
Spec	cies	Scenedesmus subspicatus		
Meth	nod	OECD 201		

Toxicity to algae (chronic)	
No data available	



Trade name: WIDOPUR-primer LF 2K - Komponente B

Current version: 2.3.0, issued: 11.06.2021 Reglaced version: 2.2.0, issued: 12.04.2021 Region: GB

Bacteria toxicity	
No data available	

12.2 Persistence and degradability

Biod	Biodegradability			
No	Product Name			
1	WIDOPUR-primer LF 2K - Komponente B			
Eval	uation	Slightly biodegradable		
Value	e	<	10	% of ThOD
Duration			28	day(s)
Method		OECD 302 C		

Phy	Physico-chemical eliminability			
No	Product Name			
1	WIDOPUR-primer LF 2K - Komponente B			
Valu	e	<	10	%
Duration			28	d
Method		OECD 302 C		

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information		
Do not discharge product unmonitored into the environment.		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer. Empty containers should be disposed of only after removing product residues adhering to container walls, by the reaction with a decontaminating solution (see item 7).

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

The product is not subject to ADR/RID/ADN regulations.

14.2 Transport IMDG

The product is not subject to IMDG regulations.

14.3 Transport ICAO-TI / IATA

The product is not subject to ICAO-TI / IATA regulations.

14.4 Other information



Trade name: WIDOPUR-primer LF 2K - Komponente B

Current version: 2.3.0, issued: 11.06.2021 Replaced version: 2.2.0, issued: 12.04.2021 Region: GB

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex

No 3

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	diphenylmethanediisocyanate, isomeres and	9016-87-9	-	56, 74
	homologues			

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances This product is not subject to Part 1 or 2 of Annex I.

15.2 Chemical safety assessment

No data available.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.



Trade name: WIDOPUR-primer LF 2K - Komponente B

Current version: 2.3.0, issued: 11.06.2021 Replaced version: 2.2.0, issued: 12.04.2021 Region: GB

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 626334