

WIDOCRYL-Topsiegel SV



Basis

Methyl methacrylate resin

Curing with hardener (at + 20°C)

Rainproof after 30 min.

Walkable after 60 min.

Consumption

Approx 500 - 700 g/m²

Basic colours

Window grey, light grey, pebble grey, ivory,
light ivory, beige, oxide red

Packaging unit

10.00 kg, 5.00 kg

Min. working temperature

-5°C

Temperature resistance

-30°C to +80°C

Cleaning in fresh condition

WIDOPAN-Cleaner

Storage

If container is kept closed and storage
temperature held constantly below
+20°C, the product may be
used for up to 6 months.

Balconies, terraces, walkways

WIDOCRYL-Topsiegel PM is used as decorative top-
ping on surfaces.

It may be used on waterproofings, primings and
wearing layers from Widopan.

WIDOCRYL-Topsiegel SV is based on methyl meth-
acrylate resin.

The surface to be sealed must be dry, clean and free
from grease and dust.

Mixing

WIDOCRYL-Topsiegel SV must be carefully stirred
before adding the hardener. Because of the short
working time, only fairly small amounts should be
mixed with hardener.

The required amount of hardener depends on the
temperature. For details see container lid.

Further details, especially regarding hazard state-
ments, security advices and measures in the event of
fire can be found in the safety data sheet under sec-
tions 2, 4, 5, 6, 7 and 8.

**Please also refer to our technical information
sheets!**