

## WIDOPAN-Mesh Fabric G120



### **Basis**

High-strength PET 1100 dtex

### **Density / specific weight**

120 g/m<sup>2</sup>

### **Thread count (Fd/cm)**

Warp 2.8 ± 0,20

Weft 2.8 ± 0,20

### **Maximum tensile strength (daN/5cm)**

Warp >100

Weft >100

### **Elongation at break (%)**

Warp 22 ± 4

Weft 23 ± 4

### **Storage**

It is essential that the product is protected from moisture. Unlimited shelf life if stored correctly.

WIDOPAN-Mesh fabric G120 is used to reinforce the sealing layer comprised of WIDOCRYL-Detail on balconies, terraces and walkways.

The WIDOPAN-Mesh fabric improves the mechanical properties of the surface seal.

The mesh fabric is laid out on the surface to be sealed and the mixture of WIDOCRYL-Detail and WIDOPAN-Hardener is applied to the surface and evenly spread with the fur roll or the smoothing cell.

Upstands and connections are made with WIDOPAN Fleece G 165 reinforcement.

Further details, especially regarding hazard statements, security advices and measures in the event of fire can be found in the safety data sheet under sections 2, 4, 5, 6, 7 and 8.

**Please also see out technical information sheets!**