

## WIDOPAN-STGM



### **Basis**

Polypropylene carbonate

### **Consumption**

1 spray bottle (0,6 kg) will do approx. 12 – 18 m<sup>2</sup>

### **Packaging unit**

Spray bottle (0,6 kg), canister (5,0 kg)

### **Colour**

Clear, transparent

### **Chemical condition**

liquid

### **Storage**

If container is kept closed and storage temperature held constantly between + 15°C and + 20°C, the product may be used for up to 6 months.

WIDOPAN-STGM is used as smoothing agent when applying the WIDOPAN-Stone carpet. It is applied to the trowel as separating agent to avoid that the binding agent in combination with the marble will stick to the trowel.

Applying the WIDOPAN-Stone carpet together with the smoothing agent does not destroy the surface tension. Using the WIDOPAN-STGM will avoid droplets forming on the marble gravel. The marble gravel will stay completely covered by the binding agent which secures a closed film on the surface. This makes the surface appear less dull.

### **Application**

During the application, the trowel is regularly moistened with the smoothing agent, e.g. by using the spray bottle.

Further details, especially regarding hazard statements, security advices and measures in the event of fire can be found in the safety data sheet under sections 2, 4, 5, 6, 7 and 8.

**Please also refer to our instructions on priming and to our technical information sheets!**