

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

WIDOPAN-FD

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Liquid plastic sealing system, pigmented

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

Widopan Produkte GmbH

Ostereichen 3

D-21714 Hammah

Telephone no. +49 (0) 4144 69821-0

Fax no. +49 (0) 4144 69821-20

Information provided by / telephone

+49 (0) 4144 69821-0

Advice on Safety Data Sheet

sdb_info@umco.de

Details of the importer

Address

Widopan Limited

System House

Horndon Industrial Park

24 Station Rd

West Horndon

Brentwood

CM13 3XL

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 3; H412

Eye Irrit. 2; H319

Flam. Liq. 3; H226

Repr. 1B; H360

Skin Irrit. 2; H315

Skin Sens. 1; H317

STOT RE 1; H372

STOT SE 3; H335

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS07



GHS08

Signal word

Danger

Hazardous component(s) to be indicated on label:

styrene

COBALT BIS(2-ETHYLHEXANOATE)

Hazard statement(s)

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H360 May damage fertility or the unborn child
 H372 Causes damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.

Hazard statements (EU)

EUH208 Contains octabenzene. May produce an allergic reaction.

Precautionary statement(s)

P201 Obtain special instructions before use.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P260 Do not breathe mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

Supplemental label elements

"Restricted to professional users"

2.3 Other hazardsPBT assessment
No data available.vPvB assessment
No data available.**SECTION 3: Composition/information on ingredients****3.1 Substances**

Not applicable. The product is not a substance.

3.2 Mixtures**Chemical characterization**

unsaturated polyester-elastomer in co-reactant diluent styrene, liquid

Hazardous ingredients

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	styrene		

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

	100-42-5 202-851-5 601-026-00-0 01-2119457861-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Asp. Tox. 1; H304 STOT SE 3; H335 STOT RE 1; H372 Aquatic Chronic 3; H412 Repr. 2; H361d	>= 25.00 - < 50.00	wt%
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics			
	- 918-167-1 - 01-2119472146-39	Aquatic Chronic 4; H413 Asp. Tox. 1; H304 EUH066 Flam. Liq. 3; H226	< 5.00	wt%
3	COBALT BIS(2-ETHYLHEXANOATE)			
	136-52-7 205-250-6 - 01-2119524678-29	Aquatic Acute 1; H400 Aquatic Chronic 3; H412 Skin Sens. 1A; H317 Eye Irrit. 2; H319 Repr. 1B; H360	< 0.50	wt%
4	octabenzene			
	1843-05-6 217-421-2 - 01-2119557833-30	Skin Sens. 1B; H317	< 0.50	wt%
5	titanium dioxide; [not containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]			
	13463-67-7 236-675-5 - 01-2119489379-17	-	< 2.50	wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

No	Route, target organ, concrete effect
1	H372 inhalational; ear; -

Acute toxicity estimate (ATE) values			
No	oral	dermal	inhalative
1			11,8 mg/l

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing. If the patient is likely to become unconscious, place and transport in stable sideways position. In case of allergic symptoms, especially respiratory tract related, seek medical help immediately.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air. Irregular breathing/no breathing: artificial respiration. Call a doctor immediately.

After skin contact

Wash off immediately with soap and water. Don't use solvents.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

Trade name: WIDOPAN-FD**Current version :** 6.2.0, issued: 27.01.2022**Replaced version:** 6.1.0, issued: 25.10.2021**Region:** GB**4.2 Most important symptoms and effects, both acute and delayed**

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Alcohol-resistant foam; Extinguishing powder; Water spray jet; Carbon dioxide

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixtureIn the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO)**5.3 Advice for firefighters**

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Wear protective clothing. Suppress gases/vapours/mists with water spray jet.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Wash hands before breaks and after work. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition.

7.2 Conditions for safe storage, including any incompatibilities

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Do not store together with: oxidizing agents

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
List of approved workplace exposure limits (WELs) / EH40			
Styrene			
	WEL short-term (15 min reference period)	1080	mg/m ³ 250 ppm
	WEL long-term (8-hr TWA reference period)	430	mg/m ³ 100 ppm
2	titanium dioxide; [not containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5
List of approved workplace exposure limits (WELs) / EH40			
Titanium dioxide total inhalable dust			
	WEL long-term (8-hr TWA reference period)	10	mg/m ³
List of approved workplace exposure limits (WELs) / EH40			
Titanium dioxide respirable dust			
	WEL long-term (8-hr TWA reference period)	4	mg/m ³
3	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
List of approved workplace exposure limits (WELs) / EH40			
Cobalt & cobalt compounds (as Co)			
	WEL long-term (8-hr TWA reference period)	0.1	mg/m ³
	Comments	Carc (cobalt dichloride and sulphate), Sen	

DNEL, DMEL and PNEC values**DNEL values (worker)**

No	Substance name	CAS / EC no	
	Route of exposure	Exposure time	Effect
1	styrene	100-42-5 202-851-5	
	dermal	Long term (chronic)	systemic
	inhalative	Short term (acut)	systemic
	inhalative	Long term (chronic)	systemic
	inhalative	Short term (acut)	local
2	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7 205-250-6	
	inhalative	Long term (chronic)	local

DNEL value (consumer)

No	Substance name	CAS / EC no	
	Route of exposure	Exposure time	Effect
1	styrene	100-42-5 202-851-5	
	oral	Long term (chronic)	systemic
	dermal	Long term (chronic)	systemic

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

	inhalative	Long term (chronic)	systemic	10.2	mg/m ³
	inhalative	Short term (acut)	systemic	174.25	mg/m ³
	inhalative	Short term (acut)	local	182.75	mg/m ³
2	COBALT BIS(2-ETHYLHEXANOATE)			136-52-7	
				205-250-6	
	oral	Long term (chronic)	systemic	55.8	µg/kg/day
	inhalative	Long term (chronic)	local	37	µg/m ³

PNEC values

No	Substance name		CAS / EC no
	ecological compartment	Type	Value
1	styrene		100-42-5 202-851-5
	water	fresh water	0.028 mg/L
	water	marine water	0.014 mg/L
	water	fresh water sediment	0.614 mg/kg dry weight
	water	marine water sediment	0.307 mg/kg dry weight
	water	Aqua intermittent	0.04 mg/L
	soil	-	0.2 mg/kg dry weight
	sewage treatment plant	-	5 mg/L
2	COBALT BIS(2-ETHYLHEXANOATE)		136-52-7 205-250-6
	water	fresh water	0.6 µg/L
	water	marine water	2.36 µg/L
	water	fresh water sediment	9.5 mg/kg dry weight
	water	marine water sediment	9.5 mg/kg dry weight
	soil	-	10.9 mg/kg dry weight
	sewage treatment plant	-	0.37 mg/L

8.2 Exposure controls**Appropriate engineering controls**

No data available.

Personal protective equipment**Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific workstation suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

State of aggregation			
liquid			
Form/Colour			
liquid			
grey			
Odour			
typical; of styrene			
pH value			
No data available			
Boiling point / boiling range			
Value	145	- 146	°C
Reference pressure		1013	hPa
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value		31	°C
Ignition temperature			
Value		490	°C
Flammability			
No data available			
Lower explosion limit			
No data available			
Upper explosion limit			
No data available			
Vapour pressure			
Value		6.24	hPa
Reference temperature		20	°C
Relative vapour density			
No data available			
Relative density			
No data available			
Density			
Value		1.02	g/cm ³
Reference temperature		20	°C
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
log Pow			2.96
Reference temperature			25 °C
Source	ECHA		

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

Viscosity			
Value	750	- 1150	mPa*s
Reference temperature		20	°C
Solvent separation test			
Value	<	3	%
Solvent content			
Value	appr.	37	%
Particle characteristics			
No data available			

9.2 Other information

Other information
No data available.

SECTION 10: Stability and reactivity**10.1 Reactivity**

No data available.

10.2 Chemical stability

No data available.

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

None, if handled according to intended use.

10.5 Incompatible materials

Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
LD50	>	5000	mg/kg bodyweight
Species	rat		
Source	CSR		
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics -		918-167-1
LD50	>	5000	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
3	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
LD50	>	3129	mg/kg bodyweight
Species	rat		
Method	OECD 425		
Source	ECHA		
Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
LD50	>	2000	mg/kg bodyweight

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

Species	rat
Method	OECD 402
Source	ECHA
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics - 918-167-1
LD50	> 2000 mg/kg bodyweight
Species	rat
Method	OECD 402
Source	ECHA

Acute inhalational toxicity (result of the ATE calculation for the mixture)

No	Product Name
1	WIDOPAN-FD
Comments	The result of the applied calculation method according to the European Regulation (EC) 1272/2008 (CLP), Paragraph 3.1.3.6, Part 3 of Annex I is outside the values that imply a classification / labelling of this mixture according to table 3.1.1 defining the respective categories (ATE for inhalation: > 20.000 ppmV (gases), > 20 mg/l (vapours), > 5 mg/l (dusts/mists).

Acute inhalational toxicity

No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
LC50		11.8	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Source	ECHA		

Skin corrosion/irritation

No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
Species	rabbit		
Source	ECHA		
Evaluation	irritant		
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics -	918-167-1	
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
3	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
Method	OECD 439		
Source	ECHA		
Evaluation	non-irritant		

Serious eye damage/irritation

No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
Species	rabbit		
Source	ECHA		
Evaluation	irritant		
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics -	918-167-1	
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	non-irritant		
3	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
Route of exposure		Skin	
Species		guinea pig	
Source		ECHA	
Evaluation		non-sensitizing	
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics -		918-167-1
Route of exposure		Skin	
Species		guinea pig	
Method		OECD 406	
Source		ECHA	
Evaluation		non-sensitizing	
3	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
Route of exposure		Skin	
Species		mouse	
Method		OECD 429	
Source		ECHA	
Evaluation		sensitizing	
Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics -		918-167-1
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Reproduction toxicity			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are met.	
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics -		918-167-1
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
Carcinogenicity			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
2	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics -		918-167-1
Source		ECHA	
Evaluation/classification		Based on available data, the classification criteria are not met.	
STOT - single exposure			
No data available			
STOT - repeated exposure			
No data available			
Aspiration hazard			
No data available			
Delayed and immediate effects as well as chronic effects from short and long-term exposure			
Inhalation of vapours may lead to headache, drowsiness and dizziness. Inhalation of vapours in higher concentration may lead to irritation of eyes, nose and respiratory tract. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.			

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

11.2 Information on other hazards**Endocrine disrupting properties**

No data available.

Other information

No data available.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
LC50		4.02	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Source	ECHA		
2	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
LC50		54.1	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	ASTM E729-96		
Source	ECHA		

Toxicity to fish (chronic)			
No	Substance name	CAS no.	EC no.
1	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
NOEC		0.21	mg/l
Duration of exposure		34	day(s)
Species	Pimephales promelas		
Method	ASTM (2002)		
Source	ECHA		

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
EC50		4.7	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
2	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
EC50		2.618	mg/l
Duration of exposure		48	h
Species	Mytilus galloprovincialis		
Method	ASTM E724-98		
Source	ECHA		

Toxicity to Daphnia (chronic)			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
NOEC		1.01	mg/l
Duration of exposure		21	day(s)
Species	Daphnia magna		
Method	OECD 211		
Source	ECHA		
2	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
NOEC		0.1697	mg/l
Duration of exposure		14	day(s)

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

Species	Aquatic oligochaeta
Source	ECHA

Toxicity to algae (acute)			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
EC50		4.9	mg/l
Duration of exposure		72	h
Species	Selenastrum capricornutum		
Method	EPA OTS 797.1050		
Source	ECHA		
2	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
EC50		0.144	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
EC10		0.28	mg/l
Duration of exposure		96	day(s)
Species	Selenastrum capricornutum		
Method	EPA OTS 797.1050		
Source	ECHA		

Bacteria toxicity			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
EC50		appr. 500	mg/l
Species	activated sludge		
Method	OECD 209		
Source	ECHA		
2	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
EC50		120	mg/l
Duration of exposure		30	min
Species	activated sludge		
Method	OECD 209		
Source	ECHA		

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
Type	ThOD		
Value		70.9	%
Duration		28	d
Method	ISO DIS 9408		
Source	ECHA		
Evaluation	readily biodegradable		
2	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
Value		60	%
Duration		10	day(s)
Method	OECD 301 B		
Source	ECHA		
Evaluation	readily biodegradable		

Abiotic Degradation			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

Type	Photolysis
Half-life	7.4 h
Source	ECHA

12.3 Bioaccumulative potential

Bioconcentration factor (BCF)			
No	Substance name	CAS no.	EC no.
1	COBALT BIS(2-ETHYLHEXANOATE)	136-52-7	205-250-6
BCF		5500	
Species		Platyhypnidium riparioides	
Source		ECHA	

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
log Pow		2.96	
Reference temperature		25	°C
Source		ECHA	

12.4 Mobility in soil

Mobility in soil			
No	Substance name	CAS no.	EC no.
1	styrene	100-42-5	202-851-5
log Koc		2.55	
Reference temperature		20	°C
Method		QSAR	
Source		ECHA	

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	No data available.
vPvB assessment	No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information**14.1 Transport ADR/RID/ADN**

Class	3
Classification code	F1
Packing group	III

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

Hazard identification no.	30
UN number	UN1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Technical name	styrene
	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
Tunnel restriction code	D/E
Label	3
Comments	Containers with a capacity <= 450 ltrs are not subject to ADR-regulations (refer to 2.2.3.1.5.)

14.2 Transport IMDG

Class	3
Packing group	III
UN number	UN1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Technical name	styrene
	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
EmS	F-E, S-E
Label	3
Comments	Containers with a capacity <= 450 ltrs are not subjected to IMDG regulations, chapter 4.1, 5.2 and 6.1 (see IMDG-Code 2.3.2.5)

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	III
UN number	UN1993
Proper shipping name	Flammable liquid, n.o.s.
Technical name	styrene
	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

Trade name: WIDOPAN-FD

Current version : 6.2.0, issued: 27.01.2022

Replaced version: 6.1.0, issued: 25.10.2021

Region: GB

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	styrene	100-42-5	202-851-5	75
2	titanium dioxide; [not containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	236-675-5	75
3	toluene	108-88-3	203-625-9	75
4	triiron-tetraoxide	1317-61-9	215-277-5	75
5	xylene	1330-20-7	215-535-7	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category:	P5c
--	-----

15.2 Chemical safety assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture.

SECTION 16: Other information
Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

EUH066	Repeated exposure may cause skin dryness or cracking.
H304	May be fatal if swallowed and enters airways.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H413	May cause long lasting harmful effects to aquatic life.

Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 21803