

WIDOCRYL-DETAIL



Detail, penetrations and roof repairs -quick, reliable, permanent solutions



Liquid waterproofing systems for sealing buildings

WIDOCRYL-Detail Liquid waterproofing systems

Roof repairs, particularly where penetrations and openings are concerned call for a rapid and reliable detail-related solution. For it is only the waterproofing of all details which guarantees permanent waterproofing success.

The material

The material base of WIDOCRYL-Detail is urethane-modified methyl methacrylate resin (PMMA), which, for work on transitional features, has been made slightly thixotropic. A polyester fleece is incapsulated for reinforcement, which in turn determines elongation at rupture and breaking strength and ensures a uniform layer thickness. It is adjusted on site to the conditions of the structural shell, thus producing an homogeneous and crack-filling waterproofing which is permanently elastic.

Possibilities of use

Detail penetrations and all kinds of roof fixtures, e.g. pipe openings, handrail supports and outlets, benefit from a reliable, long-term seal with WIDOCRYL-Detail water-proofing. WIDOCRYL-Detail will adhere to practically all bitumen, synthetic and rubber roofing sheets currently used for the waterproofing of roofs, and in most cases



WIDOPAN Produkte GmbH Finkenhörne 4a 21781 Cadenberge (Germany) Telefon +49 4777 8081-0 Telefax +49 4777 8081-20 kontakt@widopan.de www.widopan.de

Refurbishment New build

Flat roof Podium Balcony Terrace Access balcony Parking deck Detail connections Green Roof

Over 30 years of success in new build and refurbishment

without any prior priming. The reinforcement covering must be a minimum of 5 cm lap. Covering for any different materials must be determined on a case by case basis, but should not be less than 10 cm wide. WIDOCRYL-Topsiegel-PM allows the material to be colour-designed and thus to be adapted to different environments.

Rapid curing

Thanks to the addition of hardener, which will depend on temperature, WIDOCRYL-Detail will cure effectively, even at low temperatures down to $-5\,^{\circ}\text{C}$ substrate temperature. The material is rain-proof after as little as 15 minutes and will have fully cured after 30 minutes.

Approved in Europe:

WIDOCRYL-Detail is approved as a roof waterproofing material and meets the requirements of the European Construction Products Directive (CE label) and has European technical approval (ETA).



